



VYPR 4

VYPR 4 is a full-cycle top lighting solution designed for greenhouse and indoor growing environments. This new generation of the VYPR platform includes a compact form factor, increased output and even more versatility with a new wide beam optic for better uniformity at a variety of mounting heights.

SPECIFICATIONS

Light Source	LED
Spectrum	PhysioSpec™ Broad R4, R8
Output	1120 - 2760 µmol/s
Efficacy	2.7 - 3.3 µmol/J
Efficacy @50% Dimmed	2.9 - 3.6 µmol/J
AC Input Power	415W-834W @ 400V AC
AC Input Voltage	200V-480V AC, 50/60 Hz
Light Distribution	Lambertian, Wide Beam Optic (BP8)
Thermal Management	Passive
Max. Ambient Temperature	104°F [40°C]
Dimming	Source Signal Driver, 0-10V, Dim-to-off Dimming: 10%-100%
Dimming Connector and Transmission Hardware/Type	Flying Leads/M12 3-pin Male (1-Channel)
Power Factor	> 0,97 @100%
Total Harmonic Distortion	< 20%
Lifetime Q90	>50,000hrs
IP Rating	IP66; RH <90% non-condensing
Certifications	cETLus, CE, UKCA, Wet Location
Industry Standards	UL1598, UL8750, UL8800, IEC 60598-1
Warranty	5 Year Limited
Photobiological Safety IEC 62471	Risk Group 1
DLC Reported Controlled Environment	Indoor (Non-Stacked) or Greenhouse
DLC Reported Lighting Scheme	Top Light / Sole-Source or Supplemental

PHOTON FLUX AND EFFICACY @400V AC

Fixture	PhysioSpec™ Spectrum / Configuration	W AC	Output PPF (µmol/s) (400-700nm)	Output PF (µmol/s) (400-800nm)	Efficacy (PE) (µmol/J)	Efficacy (PE) (µmol/J) @50% Dim
4x	BROAD R4 (BW4) CG	422 W	1120	1150	2.7	2.9
	BROAD R8 (BP8) CG	415 W	1370	1380	3.3	3.6
	BROAD R8 (BP8) WB	415 W	1320	1330	3.2	3.5
4p	BROAD R4 (BW4) CG	634 W	1690	1730	2.7	2.9
	BROAD R8 (BP8) CG	624 W	2040	2060	3.3	3.6
	BROAD R8 (BP8) WB	624 W	1980	2010	3.2	3.5
4i	BROAD R4 (BW4) CG	825 W	2290	2340	2.8	2.9
	BROAD R8 (BP8) CG	834 W	2730	2760	3.3	3.6
	BROAD R8 (BP8) WB	834 W	2660	2690	3.2	3.5

Light Distribution: CG = Clear Glass Lens (Lambertian). WB = Wide Beam Optic.

ORDERING GUIDE

Family	Fixture	PhysioSpec™ Spectrum	Distribution	Input Voltage*	Pack Type
VR	4i	BW4	CG	LVG	B
	4p	BP8	WB	JVG	S
	4x2	2x 400 W			


- Extended lead time applies. Consult Fluence operations for details.
- Available with Broad R8 (BP8) only
- Available with VR-4p only.

Lifetime and maintenance values are given at an ambient temperature of 25 °C [77 °F]. All measured lifetimes are industry standard measurements indicating average length of operation and not a performance claim specific to any individual product




DIMENSIONS | WEIGHT

VYPR 4	Length	Width	Height	Weight
4x Light Bar 400w	23.8" 605mm	4.2" 107mm	3.6" 91mm	5.8 lbs 2.6 kg
4p Light Bar 600w	35.5" 900mm	4.2" 107mm	3.6" 91mm	8.4 lbs 3.8 kg
4i Light Bar 800w	46.1" 1170mm	4.2" 107mm	3.6" 91mm	11.7 lbs 5.3 kg




POWER SUPPLY

	Length	Width	Height	Weight
A PSU 120-277V AC 600W LVG	20" 510 mm	1.7" 44 mm	1.3" 32 mm	3.9 lbs 1.8 kg
B1 PSU 200-480V AC 600W JVG	10.4" 265 mm	5.6" 143 mm	1.9" 49 mm	6.2 lbs 2.8 kg
B PSU 200-480V AC 800W JVG	12.5" 317 mm	5.6" 143 mm	1.9" 49 mm	7.4 lbs 3.4 kg



SPECTRA



Contact **FLUENCE**


support@fluence-led.com

www.fluence.science/VYPR

© Copyright 2025 Fluence Bioengineering 2025-09

Subject to change without notice Horticultural lighting | Not suitable for household illumination.

SPECTRA



LIGHT BARS (COUPLED WITH PSU) - AMERICAS

VYPR 4 Model	Voltage	PhysioSpec™ Spectrum	Lens Type	Regional Commercial Code	Ordering PN 12NC Single Pack (-S)	Ordering PN 12NC Bulk Pack (-B)	Bulk Pack Pallet Quantity
4x2	200-480 V	Broad R4	Clear Glass	VR4X2-BW4-CG-JVG	9124 017 01932	9124 017 01933	28
		Broad R8	Clear Glass	VR4X2-BP8-CG-JVG	9124 017 01934	9124 017 01935	
			Wide Beam Optic	VR4X2-BP8-WB-JVG	9124 017 01936	9124 017 01937	
4p	120-277 V ¹	Broad R4	Clear Glass	VR-4P-BW4-CG-LVG	9124 017 02164	9124 017 02165	40
		Broad R8	Clear Glass	VR-4P-BP8-CG-LVG	9124 017 02166	9124 017 02167	
			Wide Beam Optic	VR-4P-BP8-WB-LVG	9124 017 02168	9124 017 02169	
	200-480 V	Broad R4	Clear Glass	VR-4P-BW4-CG-JVG	9124 017 01952	9124 017 01953	
		Broad R8	Clear Glass	VR-4P-BP8-CG-JVG	9124 017 01954	9124 017 01955	
			Wide Beam Optic	VR-4P-BP8-CG-JVG	9124 017 01956	9124 017 01957	
4i	200-480 V	Broad R4	Clear Glass	VR-4i-BW4-CG-JVG	9124 017 01962	9124 017 01963	32
		Broad R8	Clear Glass	VR-4i-BP8-CG-JVG	9124 017 01964	9124 017 01965	
			Wide Beam Optic	VR-4i-BP8-WB-JVG	9124 017 01966	9124 017 01967	

LIGHT BARS - EMEA/ROW

VYPR 4 Model	PhysioSpec™ Spectrum	Lens Type	Regional Commercial Code	Ordering PN 12NC Single Pack (-S)	Ordering PN 12NC Bulk Pack (-B)	Bulk Pack Pallet Quantity
4x ¹	Broad R4	Clear Glass	VR-4x-BW4-CG	9124 017 01797	9124 017 01798	56
	Broad R8	Clear Glass	VR-4x-BP8-CG	9124 017 01799	9124 017 01801	
		Wide Beam Optic	VR-4x-BP8-WB	9124 017 01802	9124 017 01803	
4p	Broad R4	Clear Glass	VR-4p-BW4-CG	9124 017 01808	9124 017 01809	40
	Broad R8	Clear Glass	VR-4p-BP8-CG	9124 017 01810	9124 017 01811	
		Wide Beam Optic	VR-4p-BP8-WB	9124 017 01812	9124 017 01813	
4i	Broad R4	Clear Glass	VR-4i-BW4-CG	9124 017 01818	9124 017 01819	32
	Broad R8	Clear Glass	VR-4i-BP8-CG	9124 017 01820	9124 017 01821	
		Wide Beam Optic	VR-4i-BP8-WB	9124 017 01822	9124 017 01823	

1. 4x2 Duo Mount (2 Lightbars: 1 PSU) require (2) 4x light bars and (1) 800 W PSU B (RCC: PJWG-V4B-800-028) per system and related PSU accessories

POWER SUPPLIES - EMEA/ROW

PSU	AC Connector Type	DC Current	Compatible Light Bars	Regional Commercial Code	Ordering PN 12NC Single Pack (-S)	Ordering PN 12NC Bulk Pack (-B)	Bulk Pack Pallet Quantity
PSU 120-277V AC 600W LVG	Wieland RST	2.13 A	VYPR 4p	PLWG-V4B-600-021 ¹	9124 017 02078	9124 017 02073	168 (Multiples of 8)
PSU 200-480V AC 600W JVG	Wieland RST	2.13 A	VYPR 4p	PJWG-V4B-680-021	9124 017 02080	9124 017 02075	168 (Multiples of 4)
PSU 200-480V AC 800W JVG	Wieland RST	2.83 A	VYPR 4i VYPR 4x2	PJWG-V4B-800-028	9124 017 01929	9124 017 01928	168 (Multiples of 4)

1. Extended leadtime applies. Consult Fluence customer service for details.

DC CABLE (Power Supply To Fixture: Not required with LVG Power Supply)

Description	Regional Commercial Code	Ordering PN 12NC Single Pack (S)	Ordering PN 12NC Bulk Pack (B)	Bulk Pack Carton Quantity
18in (0.46m) 90° Right Angle DC Cable, M19, Single Channel	CDG-VRU3P9MR9F0.5	9124 017 02086	9124 017 02081	20
3ft (0.91m) DC Cable, M19, Single Channel	CDG-VRU3P9MP9F0.9	9124 017 02087	9124 017 02082	20
6ft (1.8m) DC CBL, M19, Single Channel	CDG-VRU3P9MP9F1.8	9124 017 02088	9124 017 02083	20
T-Splitter DC Cable M19, Single Channel, Duo Mount/4x2	CDG-VRU3D9MP9F0.1	9124 017 02090	9124 017 02085	20

MOUNTING HARWARE (Light Bar)

Description	Pcs per Kit	Regional Commercial Code	Ordering PN 12NC Single Pack (-S)	Ordering PN 12NC Bulk Pack (-B)	Bulk Pack Carton Quantity
Strut/C-Channel Wire Hanger Kit (for strut width ≤ 1-5/8" / 45 mm)	2	MT-VR-US-XX	9124 016 56297	9124 016 55884	20 Kits
Pipe Wire Hanger Kit (for pipe diameter ≤ 1-3/4" / 50 mm)	2	MT-VR-PI-XX	9124 016 56295	9124 016 55877	20 Kits
Square Wire Hanger Kit (for truss width ≤ 2-3/4" / 70 mm)	2	MT-VR-SQ-XX	9124 016 56296	9124 016 55897	20 Kits
VYPR Perpendicular Mount Wire Hanger Kit (for strut 25x50 mm)	2	MT-VR-PP-XX ¹	9124 016 56288	9124 016 56020	20 Kits
VYPR Parallel Mount Bracket Kit (for strut 25x50 mm)	2	MT-V3-PL-XX ¹	9124 016 56287	9124 016 56019	20 Kits

1. Extended leadtime applies. Consult Fluence customer service for details.

MOUNTING HARWARE (Power Supply)

Description	Pcs per Kit	Regional Commercial Code	Ordering PN 12NC Single Pack (-S)	Ordering PN 12NC Bulk Pack (-B)	Bulk Pack Carton Quantity
PSU Universal Strut Mount Hanger Kit MGS (PSUs A, B, B1)	2	MT-V4-UL-MGS	9124 017 02093	9124 017 02091	20 Kits
Power Supply Surface Mount Kit, 600/800W, JVG only	2	MS-PS-MB-JV ¹	9124 017 02585	9124 017 02586	10 Kits

1. Extended leadtime applies. Consult Fluence operations for details.

MOUNTING HARWARE (Combo)

Description	Pcs per Kit	Regional Commercial Code	Ordering PN 12NC Single Pack (-S)	Ordering PN 12NC Bulk Pack (-B)	Bulk Pack Carton Quantity
Combo Hanger Kit, 600/800W, JVG only	2	MT-V4-CB-JV	9124 017 02587	9124 017 02588	20 Kits

AC POWER CABLE (Power Supply to AC Line)

AMERICAS (AC Line to Luminaire)	Regional Commercial Code	Ordering PN 12NC Single Pack (S)	Ordering PN 12NC Bulk Pack (B)	Bulk Pack Carton Quantity
6ft AC Pigtail with Wieland Connector	CAA-XXU3WGFL3X1.8	9124 017 01601	9124 016 56071	10
15ft AC Pigtail with Wieland Connector	CAA-XXU3WGFL3X4.6 ¹	9123 000 02588	9124 016 56072	5
6ft AC Cable Wieland Connector with L7-15P plug (max 277 V)	CAA-XXU3WGFL7P1.8 ¹	9124 017 01602	9124 016 56069	10
15ft AC Cable Wieland Connector with L7-15P plug (max 277 V)	CAA-XXU3WGFL7P4.6 ¹	9123 000 02486	9124 016 56070	5
EMEA (AC Line to Luminaire)				
0.8m AC Cable Dca Pigtail with Wieland Connector	RST20I3GDCAPTC80CM	-	9124 017 02496	10
REST OF THE WORLD (AC Line to Luminaire)				
0.9m (3ft) AC Cable H07RN-F Pigtail with Wieland Connector ²	CAE-XXH3WGFL3X0.9 ¹	9124 016 56073	9124 016 56074	10
1.8m (6ft) AC Cable H07RN-F Pigtail with Wieland Connector ²	CAE-XXH3WGFL3X1.8 ¹	9124 016 56075	9124 016 56076	10

1. Extended leadtime applies. Consult Fluence operations for details.

2. For markets using harmonized cable

Contact **FLUENCE** 

support@fluence-led.com 

www.fluence.science/VYPR 



© Copyright 2025 Fluence Bioengineering 2025-09

Subject to change without notice Horticultural lighting | Not suitable for household illumination.

DIMMING SIGNAL CABLE (Power Supply to Dimming Control)

AMERICAS (Dimming Control to Power Supply)	Regional Commercial Code	Ordering PN 12NC Single Pack (S)	Ordering PN 12NC Bulk Pack (B)	Bulk Pack Carton Quantity
11 IN (0.28m) Dimming Signal Cable, Pigtail, M12 Connector	CCA-XXU3T2FL3X0.3	9124 017 01621	9124 016 55902	10
5 FT (1.52m) Dimming Signal Cable, Pigtail, M12 Connector	CCA-XXU3T2FL3X1.5	9124 017 01622	9124 016 55881	10
EMEA/REST OF THE WORLD (Dimming Control to Power Supply)				
0.8m Dimming Signal Cable, Cca, Pigtail, M12 Connector	CCE-XXC3T2FL3X0.8	9124 017 01623	9124 016 55883	10

CABLE ADAPTERS

ACCESSORIES	Regional Commercial Code	Ordering PN 12NC Single Pack (S)	Ordering PN 12NC Bulk Pack (B)	Bulk Pack Carton Quantity
AC Connector Adapter for Power Supply, Male Wieland Black to Female Leaf Green, Wieland Part #: 99.656.0000.7	AAA-XXU3WGFWMXXX	9123 000 02483	9124 016 56112	20
AC adapter Cable for Wieland to M19 FLEX (Americas only)	AAA-XXU3WGFPM0.1	9124 017 01608	9124 016 56068	20

NOMINAL ELECTRICAL AC INPUT

FIXTURE	PhysioSpec™ Spectrum	AC VOLTAGE	120 V	208 V	230 V	277 V	347 V	400 V	480 V
4x2	Broad R4	AC Current	-	4.05 A	3.78 A	3.03 A	2.40 A	2.10 A	1.75 A
		AC Power	-	845 W	844 W	840 W	834 W	841 W	841 W
	Broad R8	AC Current	-	3.99 A	3.72 A	2.99 A	2.38 A	2.07 A	1.73 A
		AC Power	-	832 W	831 W	827 W	825 W	827 W	828 W
4p	Broad R4	AC Current	5.37 A	3.08 A	2.83 A	2.27 A	1.81 A	1.57 A	1.31 A
		AC Power	644 W	634 W	633 W	630 W	628 W	629 W	629 W
	Broad R8	AC Current	5.29 A	3.03 A	2.79 A	2.24 A	1.78 A	1.55 A	1.29 A
		AC Power	634 W	625 W	623 W	621 W	619 W	620 W	620 W
4i	Broad R4	AC Current	-	4.09 A	3.77 A	3.02 A	2.40 A	2.09 A	1.75 A
		AC Power	-	842 W	841 W	837 W	834 W	837 W	838 W
	Broad R8	AC Current	-	4.06 A	3.74 A	3.00 A	2.39 A	2.08 A	1.73 A
		AC Power	-	836 W	835 W	830 W	828 W	831 W	832 W

* At 77°F (25°C) ambient temperature